

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
27 January 2005 (27.01.2005)


PCT

(10) International Publication Number  
**WO 2005/007440 A1**

- (51) International Patent Classification<sup>7</sup>: **B60K 6/04** (74) Agent: ITEC INTERNATIONAL PATENT FIRM; Pola-Nagoya Bldg., 9-26, Sakae 2-chome, Naka-ku, Nagoya-shi, Aichi 4600008 (JP).
- (21) International Application Number: PCT/JP2004/008694
- (22) International Filing Date: 15 June 2004 (15.06.2004) (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 2003-200030 22 July 2003 (22.07.2003) JP
- (71) Applicant (for all designated States except US): TOYOTA JIDOSHA KABUSHIKI KAISHA [JP/JP]; 1, Toyota-cho, Toyota-shi, Aichi 471857 (JP).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): HOSHIBA, Takeshi [JP/JP]; c/o Toyota Jidosha Kabushiki Kaisha, 1, Toyota-cho, Toyota-shi, Aichi 471857 (JP). NADA, Mitsuhiro [JP/JP]; c/o Toyota Jidosha Kabushiki Kaisha, 1, Toyota-cho, Toyota-shi, Aichi 471857 (JP).
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: POWER OUTPUT APPARATUS FOR HYBRID VEHICLE



(57) Abstract: A hybrid vehicle of the invention has an engine, a planetary gear unit including a carrier linked with rankshaft of the engine and a ring gear linked with a drive shaft, a motor MG1 inputting and outputting power to and from a sun gear of the planetary gear unit, and a motor MG2 inputting and outputting power to and from the drive shaft. During a drive of the hybrid vehicle in a light load state and under a drive restriction of the motor MG2, the hybrid vehicle corrects a target revolution speed  $N_{e^*}$  of the engine to make a calculated average charge-discharge electric power  $W_{bave}$  of a battery equal to a charge-discharge electric power demand  $W_{b^*}$ , while keeping a torque of the engine unchanged (steps S300 to S330), and controls actuation of the engine and the motors MG1 and MG2.



**Published:**

— with international search report

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*